



Digital Audio Surround Sound Receiver Package

- Upgrade your DVD player into a complete Digital Home Cinema System
- 6-Speaker Package with 50W Subwoofer and 5 compact 2-way Satellite speakers (customized acoustical speaker design!)
- 350 Watts Surround Power Output:
 5 x 60 Watts equal power per channel, and 50 Watts Powered Subwoofer
- Digital Sound Processing via DUET CORE
- · 10 Audio Input connections in total
- 3 Digital Inputs (2 coax, 1 optical) and a Digital Output (coax) for Digital (CD) Recordings from multiple analogue or digital sources including DVD!
- · 3 Video Input Connections and 2 Outputs
- 6 Channel Input terminal (DVD Audio and Super-Audio CD prepared)
- Virtual 3D Surround for Simulated Surround Sound without Rear Speakers
- · 'Hall' feature for normal stereo with rear speaker sound
- All Dolby surround Modes and Delay Times
- Equalizer smart sound modes: Personal, Speech, Music, Movie, Multi-Media
- Screw terminals for Left, Right and Center speaker connections
- 51-key Audio/Video MultiBrand Universal Remote Control
- Menu Navigator Rotary Knob for quick set-up
- Speaker wall-brackets, digital audio cable for DVD hook-up and quick installation card included































PHILIPS





Sound Enhancement

Dolby Digital Surround Sound - Available on DVD, Laserdisc*, satellite broadcasts, Cable and as the standard for HDTV, Dolby Digital® offers the ultimate experience in home theater surround with six discrete channels of digital nome theater surround with six discrete channels of digital CD sound. Discrete means that each channel carries its own sound and depending on what happens on screen each speaker plays its own unique role in providing the right sound. Front left, center and right join two surround speakers to reproduce highs, mid and bass frequencies in the full care placease of forecast Dependencies in speakers to reproduce high, filled allo dass irequenties in five full-range channels of surround. Bass rumble, explosions and low frequency effects you feel are delivered through a dedicated sixth, subwoofer channel. Also known as AC-3 and Dolby 5.1, Dolby Digital® delivers the expanded sense of depth, localization and overall realism which was formerly between the production of the surround engineer of the production of t only known from digital surround sound equipped cinemas.

6-speaker package - No less then 5 compact 2-way satellite loudspeakers to build your personal cinema on a stand or wall-mounted with the enclosed wall-brackets. The five speakers are acoustically specially designed to match the tonal characteristics of the receiver. Front left, right and center speaker are magnetically protected to prevent any interference with television picture tube purity. The sixth speaker is a 50 watt powered subwoofer.

350W surround power output - The five, 3x60W (left, right, center) and 2x60W (rear), receiver amplifiers together with the 50W subwoofer amplifier deliver 350 Watts of with the 50W subwoofer amplifier deliver 350 Walts of home theater power. The stereo output power of 50W per channel is specified at 6 Ohm, 40Hz-20KHz and 0.7% total harmonic distortion (THD). The amplifiers have been designed with special attention to a short 'rise' and 'fall' time, so characteristic for the frequent and sudden drastic changes in dynamics of movie sound in general. Furthermore, the amplification reserves are designed such that they are more than sufficient to follow sudden needs for more sound pressure. for more sound pressure.

50 W powered subwoofer - Subwoofers add dynamism to normal music and motion pictures. It sets the stage for a more intense sensation. The 50W Philips subwoofer features a down-firing 61/2" woofer to reflect sound waves off the floor, thereby adding impact. In all, the subwoofer is sufficiently power packed to generate that cinema essential sonic sound boom

Digital Sound Processing via *DUET CORE* - Philips Semiconductors is highly specialized in digital sound processing. One of their crown DSP (digital sound processing) ICs is the 'DUET'. The DUET's huge processing power of 80 MIPS (million instructions per second) assures the highest processing power of the processi the highest possible accuracy in digital audio processing. Other characteristics are automatic detection of source (AC-3, MPEG or PCM audio) and smooth (clicking free) automatic switching between coding formats. Furthermore DUET carries digital bass cross-over filters (for subwoofer signal) and 3rd generation virtualizer algorithms for highly realistic virtual Dolby, Lastly, DUET has the unique capability of translating Dolby Digital multi-channel sound into a stereo signal suitable for digital recording onto e.g. CD-R.

Virtual 3D Surround / Virtual Dolby® Surround - A Obly Surround Playback system delivers amazingly rich and convincing surround sound from only the two (or three) front speakers. The Pro-Logic or Dolby Digital® surround channel is processed by a 'virtualizer' DSP to add the surround effect from just the front speakers. The Philips virtualizer algorithm on the 'DUET' DSP is the current state of the act formers for which the procession of of the art reference for virtual surround sound processing.

'Hall' feature - For use with non-surround sound sources in order to create a cinema effect through normal stereo with rear speaker sound. This 'simulated' surround provides an extra musical ('live') ambience to stereo sound.

Equalizer Smart Sound - Has 5 modes, specially designed to match the sound of various TV (and Audio) programs. 'Speech' is used for news, discussions and talk show programs. 'Music' is used for music programs. 'Movie' is used for movies or TV-series or soaps. 'Multi-Media' is used when video games are connected to the TV. 'Personal' corresponds with the bass and treble setting chosen by the

Screw terminals - For left , right and center speaker connection ensures a loss-less flow of electrical signals from the set to all main loudspeakers.

Convenience

Digital inputs and output - 3 digital inputs (2 coax, 1 optical) are foreseen to connect digital sound sources (e.g. opitical) are to research of continect digital TV). A digital output connection (coax) is foreseen to enable digital (CD) recordings from any of the digital inputs. The output can provide a down-mixed (stereo) DVD multi-channel sound signal in order to record from DVD to e.g. CD-R.

Stereo Downmix - The digital output will automatically provide a stereo downmix in case a multichannel signal is detected at any of the digital input connectors. In that way digital audio recordings can be made from movie DVD's (e.g. Live concerts from music DVD's)

Night mode - Establishes dynamic range compression of digital sound to reduce the volume differences between the loud and soft passages in source material with digital surround sound where sound level differences can be so dramatic. This feature is especially useful at night when you don't want to disturb the neighbors or wake up the kids!

Video Connections - 3 video input connections and 2 outputs (incl. monitor) are foreseen to hook up video sources. As these video inputs switch simultaneously with the audio inputs, correct picture with correct sound is

6 Channel input - Six input selectors at the back of the set allow to connect to any type of multichannel decorder. Be it DTS, DVD Audio or Super Audio CD. The 6 Channel input makes your system future proof!

Easy hook up - With color coded speaker connections for quick and easy connection of all loudspeakers. By using distinct colors for each of the speaker connection terminal on the speaker and on the set, and using the same color for the cable, the chance of faulty connection (and customer complaints) are practically approx complaints) are practically zero!

51-key Audio/Video Multi Brand Universal remote **control** - To operate all main receiver functions and Philips, Magnayox or any other mainstream branded CD player, tape Magnavox of any other mainstream oranged CD player, tape deck, VCR, television and DVD player, Satellite or cable boxt The remote will operate your non-Philips/Magnavox equipment by simply entering a code from the instruction manual in the remote control. The remote has a clear ergonomically designed lay-out (see picture)

30 tuner presets with station name display - Th available tuner presets can be randomly used to store AM and FM stations (30 in total). Each of the presets can be given a user defined name of up to 8 characters. Giving the preset a name is as easy as 1-2-3 with the menu navigator.

Tuner sensitivity adjustment - The tuner sensitivity to pick up radio stations can be set to high and low. In case of low, only the 'strong' stations will be picked up during a search. When even some of the weaker stations are of interest, the 'low' option will pick up every station the tuner can possibly receive.

Display brightness adjustment - Conveniently adjusts the brightness of the display in 3 steps.

2 switched mains outlets - Allows to connect another HiFi component. Switching the receiver to standby will automatically switch off the connected set.

Standby power <2W - To help save energy consumption, the standby transformer of this set has been designed not to consume more than 2 Watt in standby mode.

Design

Display - Color and graphic/character size are defined such that at visibility remains clear even at larger distances.

· Audio inputs/outputs 7 analogue input sources, 3 analogue output connections

CD CDR/Tape · in/out

SAT VCR in/out 6 CH/DVD

DVD see digital audio inputs/outputs Headphone

3 digital input sources. Digital audio in/output 1 digital output connection

- 1 optical slink to connection 1 digital coax connection · OUT 3 input sources. Video inputs/outputs 2 output connections

- SAT in: in/out Monitor

Speaker Connections suitable for speakers 6 Ohm : screw type connection : click-fit connection left right center

rear left, right Miscellaneous connections

- Cinema Link System control bus - subwoofer pre-out center pre-out

mains outlet switched 2x AM antenna : loop type : click-fit 300 Ohm - FM antenna

UPC Code: t.b.c 17.2" W x 5.3" H x 13.8" D (receiver) 3.8" W x 6.2" H x 3.5" D (I/r, center + surround) 10.0" W x 3.8" H x 3.5" D (center speaker) 7.9"W x 12.2" H x 14.6" D (subwoofer) Product weight: t.b.c. (receiver)


Package Dimension: t.b.c. Total package weight : t.b.c. Container loading : t.b.c. Country of orgin: China

Carton contains: receiver FR965/17, remote control, batteries, instruction for use, AM + FM antenna, quick installation card, warrantee information, 6 loudspeakers (incl. subwoofer), loudspeaker cable (L/R: 2x9ft, C: 1x9ft, S: 2x33ft.), subwoofer mains + connection cable, 'Cinema Link' cable, digital audio cable for DVD connections

Printed in Singapore Date printed : Aug 2000 © 2000 Royal Philips Electronics N.V. All rights reserved. A Division of Philips Electronics North America Corp. Specifications subject to change without notice. Dolby, Dolby Digital®, Dolby ProLogic® and the double-D symbol are trademarks of Dolby Laboratories

As an ENERGY STAR® Partner, Phillips has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.

* Dolby Digital laserdisc use requires optional AC-3 RF demodulator



PHILIPS

